

TECHNICAL DATASHEET




EF TAPPING SADDLE

04 Update - 01/2023

TECHNICAL DATA

| | |
|-----------------------|-------------------|
| Article No | 001 117 2071 0053 |
| d (mm) | 50 |
| d1 (mm) | 25 |
| le (mm) | 75 |
| h (mm) | 135 |
| h1 (mm) | 43 |
| Z (mm) | 113 |
| L (mm) | 120 |
| Weight (Kg) | 0,330 |
| Box Quantity (pcs) | 30 |
| Box Dimension (cm) | 55x30x36 |

INJECTION MOULDED



IDENTIFICATION OF PRODUCT

| | |
|----------------|-------------------------|
| D(mm) | 50-25 |
| SDR | 11 |
| RAW MATERIAL | PE 100 |
| PRESSURE CLASS | 16 Bar Water 10 Bar Gas |
| TRADEMARK | NTG |
| EXECUTION | Injection Moulded |
| STANDARD | EN 12201-3 |

EN 1555-3
AS / NZS 4129
Suitable for SDR11 pipe
Injected monobloc type
4 mm pin connectors
Long Fusion outlet
Hexagon wrench 12 mm
O-ring sealed screw cap

SPECIFICATION

EF SPECIFICATION

| | |
|-----------------|---------------|
| WELDING VOLTAGE | 40 V |
| RESISTANCE | 10,5 Ω |
| WELDING TIME | 45 Sec. |
| COOLING TIME | 10 Min. |
| WINDING TYPE | Monofilar |
| WELDING BARCODE | |



941420311252401055045116

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance $\pm 5\%$. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.