

TECHNICAL DATASHEET




EF TAPPING SADDLE

04 Update - 01/2023

TECHNICAL DATA

Article No	001 117 2071 0095
d (mm)	90
d1 (mm)	32
le (mm)	76
h (mm)	195
h1 (mm)	65
Z (mm)	120
L (mm)	140
Weight (Kg)	0,700
Box Quantity (pcs)	12
Box Dimension (cm)	55x30x36

INJECTION MOULDED



IDENTIFICATION OF PRODUCT

D(mm)	90-32
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3

SPECIFICATION	Suitable for SDR11....17 pipe
	Injected monobloc type
	4 mm pin connectors
	Long Fusion outlet
	Hexagon wrench 17 mm
	O-ring sealed screw cap

EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	7,0 Ω
WELDING TIME	140 Sec.
COOLING TIME	15 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	



941420322193407005140119

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance $\pm 5\%$. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.

Fr 161 Rev 00